





## DIMENSIONS

Height to –	
A. Top of ROPS cab .....	109.7" (2785 mm)
B. Wheelbase .....	92.5" (2350 mm)
C. Ground clearance .....	14" (360 mm)
D. Angle of departure .....	35°
Width –	
Overall* w/o bucket .....	77.9" (1978 mm)
Centerline tread .....	60" (1526 mm)
Turning radius* – outside .....	162.7" (4132 mm)
Turning angle –	
From center .....	41°
Total angle .....	82°
Rear axle oscillation, total .....	24°

NOTE: \*Dimensions taken with 405/70 R20 tires. Additional dimensions on pages 3 & 4.

## WEIGHT ADJUSTMENTS

Select Options	Weight Adjustment	Tipping Load Adjustment Straight	Tipping Load Adjustment 40° Turn
Optional 396 lb (180 kg) counterweight .....	396 lb (180 kg) .....	497 lb (226 kg) .....	391 lb (177 kg)

NOTE: \*\*Unit equipped with Z-Bar loader arms, 1.31 yd<sup>3</sup> (1.0 m<sup>3</sup>) general purpose pin on bucket w/bolt-on edge, 405/70 R20 tires, ROPS cab with heater, standard counterweight, standard batteries, front and rear fenders, full fuel and 165 lb (75 kg) operator. Adjust select options from rated weight.

# PERFORMANCE DATA

21D Z-Bar	1.44 yd <sup>3</sup> GP (1.10 m <sup>3</sup> ) Bucket w/Bolt-on Edge	1.44 yd <sup>3</sup> GP (1.10 m <sup>3</sup> ) Bucket w/Teeth & Segments
SAE bucket capacity – struck .....	1.20 yd <sup>3</sup> (0.92 m <sup>3</sup> ) .....	1.20 yd <sup>3</sup> (0.92 m <sup>3</sup> ) .....
Heaped .....	1.44 yd <sup>3</sup> (1.10 m <sup>3</sup> ) .....	1.44 yd <sup>3</sup> (1.10 m <sup>3</sup> ) .....
Bucket width – outside .....	82.7" (2100 mm) .....	82.7" (2100 mm) .....
Bucket weight .....	1,069 lb (485 kg) .....	981 lb (445 kg) .....
E. Operating height – fully raised w/spillguard .....	167.5" (4254 mm) .....	167.5" (4254 mm) .....
F. Hinge pin height – fully raised .....	131.7" (3344 mm) .....	131.7" (3344 mm) .....
G. Overall length – bucket level on ground .....	217.8" (5531 mm) .....	219.6" (5578 mm) .....
Dump angle – fully raised .....	42° .....	42° .....
H. Dump height – fully raised, 45° dump .....	104.7" (2659 mm) .....	103.5" (2629 mm) .....
J. Bucket reach – fully raised, 45° dump .....	35.0" (889 mm) .....	37.0" (941 mm) .....
K. Bucket reach – 7'0" (2.13 m) height, 45° dump .....	49.3" (1253 mm) .....	50.6" (1285 mm) .....
Operating load – SAE .....	3,864 lb (1753 kg) .....	3,843 lb (1743 kg) .....
Maximum material density – SAE .....	2,686 lb/yd <sup>3</sup> (1593 kg/m <sup>3</sup> ) .....	2,671 lb/yd <sup>3</sup> (1585 kg/m <sup>3</sup> ) .....
Tipping load – SAE		
Straight .....	9,496 lb (4307 kg) .....	9,426 lb (4275 kg) .....
40° turn .....	7,728 lb (3506 kg) .....	7,686 lb (3486 kg) .....
Lift capacity –		
Full height .....	7,402 lb (3357 kg) .....	7,491 lb (3398 kg) .....
Maximum reach .....	9,393 lb (4261 kg) .....	9,480 lb (4300 kg) .....
Ground .....	12,571 lb (5702 kg) .....	12,642 lb (5734 kg) .....
Breakout force w/tilt cylinder .....	15,921 lb (7222 kg) .....	16,904 lb (7667 kg) .....
Maximum rollback –		
Ground .....	48° .....	47° .....
Carry position .....	52° .....	52° .....
@ Maximum reach .....	60° .....	60° .....
@ Full height .....	59° .....	59° .....
Dig depth .....	3.5" (88 mm) .....	2.9" (73 mm) .....
L. Maximum grading angle w/bucket – back dragging .....	62° .....	63° .....
Loader clearance circle .....	360.6" (9158 mm) .....	361.4" (9179 mm) .....

<b>1.31 yd<sup>3</sup> GP (1.00 m<sup>3</sup>) Bucket w/Bolt-on Edge</b>	<b>1.31 yd<sup>3</sup> GP (1.00 m<sup>3</sup>) Bucket w/Teeth &amp; Segments</b>
1.10 yd <sup>3</sup> (0.84 m <sup>3</sup> )	1.10 yd <sup>3</sup> (0.84 m <sup>3</sup> )
1.31 yd <sup>3</sup> (1.00 m <sup>3</sup> )	1.31 yd <sup>3</sup> (1.00 m <sup>3</sup> )
82.7" (2100 mm)	82.7" (2100 mm)
1,058 lb (480 kg)	970 lb (440 kg)
167.5" (4254 mm)	167.5" (4254 mm)
131.7" (3344 mm)	131.7" (3344 mm)
217.8" (5531 mm)	219.6" (5578 mm)
42°	42°
104.7" (2659 mm)	103.5" (2629 mm)
35.0" (889 mm)	37.0" (941 mm)
49.3" (1253 mm)	50.6" (1285 mm)
3,887 lb (1763 kg)	3,929 lb (1782 kg)
2,972 lb/yd <sup>3</sup> (1763 kg/m <sup>3</sup> )	3,004 lb/yd <sup>3</sup> (1782 kg/m <sup>3</sup> )
9,550 lb (4332 kg)	9,633 lb (4370 kg)
7,775 lb (3527 kg)	7,858 lb (3564 kg)
7,401 lb (3357 kg)	7,491 lb (3398 kg)
9,410 lb (4268 kg)	9,498 lb (4308 kg)
12,639 lb (5733 kg)	12,712 lb (5766 kg)
15,955 lb (7237 kg)	16,934 lb (7681 kg)
48°	47°
52°	52°
60°	60°
59°	59°
3.5" (88 mm)	2.9" (73 mm)
62°	63°
360.6" (9158 mm)	361.4" (9179 mm)

## **INSTRUMENTATION**

---

Electronic Information Center  
Displays/Gauges –  
Speedometer  
Fuel level  
Hourmeter  
Indicator lights –  
Hydraulic oil temperature  
Voltmeter  
Work lights  
Loader control lockout  
Brake pressure  
Master indicator  
Parking brake  
Air conditioning\*  
Air filter restriction  
Direct selected F/N/R  
Gear selected  
Gear position  
Turn signal indicator  
Engine coolant temperature  
Engine oil pressure  
Audible alarms –  
Caution alarm  
Critical alarm  
Backup alarm  
Horn

NOTE: \*If equipped with option.

## **OPERATOR ENVIRONMENT**

---

Cab w/heat  
Key start  
Articulated power steering  
w/tilt column  
Fully adjustable, cloth  
suspension seat  
Foot throttle  
Single lever electronic speed shift  
control, F/N/R switch in loader  
control handle  
Cup holder  
Retractable seat belt  
Storage tray  
Sun screen front & rear  
Defroster  
Sliding side window  
Dome light  
Wipers rear & front  
12-volt auxiliary power  
Lighter, 12-volt  
External rearview mirrors  
R.H. steps  
Coat hook

## **LOADER**

---

Z-bar loader linkage  
Single control for lift and tilt  
Positive hold float  
Automatic return-to-dig  
Bucket position indicator on bucket  
Hydraulic attachment coupler

## **CYCLE TIME**

---

Raise w/rated bucket load..... 6.6 sec  
Dump w/rated bucket load  
Z-Bar ..... 1.1 sec  
Lower (empty)  
Float down ..... 3.5 sec

## **SERVICE CAPACITIES**

---

Fuel tank ..... 26 gal (100 L)  
Hydraulic system  
Total ..... 18.2 gal (70 L)  
Reservoir ..... 10.5 gal (40 L)  
Front and rear axle  
Total axle (each) ..... 4 qt (3.7 L)  
Engine oil w/filter ..... 8 qt (7.5 L)  
Cooling system  
-36° F (-38° C) ..... 3.4 gal (13 L)

## **OPERATING WEIGHTS**

---

### **Z-Bar**

Unit equipped with ROPS cab with  
heater, standard counterweight,  
405/70 R20 Dunlop tires, front  
and rear fenders, 1.31 yd<sup>3</sup> (1.0 m<sup>3</sup>)  
general purpose loader bucket  
w/edge, full fuel, 165 lb (75 kg)  
operator ..... 12,896 lb (5849 kg)

## STANDARD EQUIPMENT

---

### OPERATOR'S ENVIRONMENT

See page 5

### ENGINE

Perkins 704-30

Fuel filter w/water trap

Dual element air cleaner

65 amp alternator

(1) 750 CCA 12-volt battery

Liquid-cooled radiator

Non spark-arresting muffler

### LOADER

See page 5

### DRIVETRAIN

4-wheel drive

Hydrostatic transmission

Single lever electronic speed shift control, F/N/R switch in loader control handle

Outboard planetary axles

Conventional differentials

Transmission oil cooler

Hydraulic wet disc brakes

Mechanical parking brake

### HYDRAULICS

3-spool loader control valve

(8) Diagnostic quick couplers

Secondary steering

### OTHER

Front and rear fenders

Lights –

(2) Front driving headlights

(high/low beam)

(2) Front flood

(2) Stop/tail lights and backup light

(2) Rear flood

Front and rear turn signal/flash

Drawbar hitch

Articulation locking bar

Lift and tie-down points – front/rear

Backup alarm

## OPTIONAL EQUIPMENT

---

### OPERATOR'S COMPARTMENT

Cab air conditioning w/heater

Radio

Rotating beacon

Limited slip rear axle

### LOADER

Attachment auxiliary hydraulics

Bucket position indicator

Buckets (see page 3 & 4)

### HYDRAULICS

Auxiliary hydraulics

Load holding control device

### TIRES

405/70 R20 EM SPT9

405/75 R20 XM27

14.5 x 20 MPT E91

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

Form No. CE 293-03-02

Replaces Form No. CE 293-08-01

IMPORTANT: Case Corporation reserves the right to change these specifications without notice and without incurring any obligation relating to such change.

Visit Case Construction on the Web at:  
<http://www.casece.com>

Printed in U.S.A.

© 2002 CASE CORPORATION. All Rights Reserved.  
Case and 4 IN 1 are registered trademarks of Case Corporation. ACS and Pro Series 2000 are registered trademarks of ACS Industries, Inc.

### CASE CONSTRUCTION EQUIPMENT CONTACT INFORMATION

#### NORTH AMERICA/MEXICO:

700 STATE STREET  
RACINE, WISCONSIN 53404

#### LATIN AMERICA:

AV. GENERAL DAVID SARNOFF 2237  
32210 – 900 CONTAGEM – MG  
BELO HORIZONTE BRAZIL

#### EUROPE/AFRICA/MIDDLE EAST:

18, PLACE DES NYMPHEAS  
ZI PARIS NORD 11 95915  
ROISSY CDG CEDEX FRANCE

#### ASIA PACIFIC:

31-67 KURRAJONG ROAD  
ST. MARY'S  
NEW SOUTH WALES 2760 AUSTRALIA

